



## TOMLINE

- ✓ High lumens available up to 150 lm/w
- ✓ High luminous flux up to 30000 lm
- ✓ Excellent heat dissipation due to aluminum body
- ✓ Long lifetime due to high quality LED chips and drivers
- ✓ D-MARK tested for paper production, wood processing



## CLEANLINE

- ✓ Dust-free design, the best choice for food processing and heavy industry
- ✓ Easy for cleaning, can be washed by highpressure water no any glass components, ideal for food industry
- ✓ EU Patent Design



MODEL No.	T10C-60W	T10C-100W	T10C-120W	T10C-150W	T10C-180W	T10C-200W
DIMENSIONS (mm) (l,w,h)	605x135x72		905x135x72		1205x135x72	
POWER	60w	100W	120W	150W	180W	200W
VOLTAGE	AC100-277V / 100-350V / 277-480V // 50-60Hz					
CCT (K)	3000K		4000K	5000K	6000K	
LUMINOUS EFFICIENCY (lm/W)	130 lm/W (150 lm/W lumen plus optional)					
LUMINOUS FLUX (lm) STANDARD	7800 lm	13000 lm	15600 lm	19500 lm	23400 lm	26000 lm
LUMINOUS FLUX (lm) LUMEN PLUS	9000 lm	15000 lm	18000 lm	22500 lm	27000 lm	30000 lm
CRI	Ra > 70 (Ra > 80 optional)					
BEAM ANGLE	120°					
IP GRADE PROTECTION	IP65					

This Linear Highbay light TOMLINE series was specially designed for industrial environments. The massive aluminum body provides excellent cooling performance and make sure a long lifespan of LED chips and low light decay from them. The large and break-resistant polycarbonate cover provides a perfect light distribution. This product is an ideal replacement for all sorts of traditional industrial lamps. For different applications this item is available in three versions: standard, lumen plus, and dust free version.

### OPTIONS AVAILABLE

CRI 80 Ra  
DIMMABLE 1-10V  
DALI  
MICROWAVE MOTION SENSOR  
EMERGENCY POWER SUPPLY  
ZIGBEE

MODEL No.	T12C-60W	T12C-100W	T12C-150W	T12C-200W
DIMENSIONS (mm) (l,w,h)	605*135*72	905*135*72	1205*135*72	1505*135*72
POWER	60W	100W	150W	200W
VOLTAGE	AC100-277V // 50-60Hz			
CCT (K)	3000K		4000K	5000K 6000K
LUMINOUS EFFICIENCY (lm/W)	130 lm/W (155lm/W LUMEN PLUS optional)			
LUMINOUS FLUX (lm) STANDARD	7800 lm	13500 lm	20000 lm	27000 lm
LUMINOUS FLUX (lm) LUMEN PLUS	9300 lm	15500 lm	23250 lm	31000 lm
CRI	Ra >80			
BEAM ANGLE	120°			
IP GRADE PROTECTION	IP65			

Not only with all features of T10B design, the T12C is also a special dust-free designe with a back cover, which allow you to wash by high pressure water gun. Without any glass components, it is a ideal choice for food processing and heavy industry.

### OPTIONS AVAILABLE

1-10V DIMMABLE  
CRI 90 RA AVAILABLE UPON REQUEST  
IF REQUESTED A CLEAR COVER CAN BE PROVIDED  
MICROWAVE SENSOR FUNCTIONS OPTIONAL