

150lm/W
O - Line Serie

PERFEKT LICHT

LED Lichtband-System



Trunking Rail

5 Wire: L1, L2, L3, N,FG

7 Wire: L1, L2, L3, N, FG + 2 wires for Dimming

11 Wire: L1, L2, L3, N, FG + 2 wires for Dimming
+ 4 wires for Emergency converter & Battery

Color Option: WH(White), BK(Black), SV(Silver)



Length	Discription	Code No.	VIP
570mm	5 Wire	CST-06X ₁ -05X ₂	
	7 Wire	CST-06X ₁ -07X ₂	
	11 Wire	CST-06X ₁ -11X ₂	
1416mm	5 Wire	CST-15X ₁ -05X ₂	
	7 Wire	CST-15X ₁ -07X ₂	
	11 Wire	CST-15X ₁ -11X ₂	
2832mm	5 Wire	CST-30X ₁ -05X ₂	
	7 Wire	CST-30X ₁ -07X ₂	
	11 Wire	CST-30X ₁ -11X ₂	
4248mm	5 Wire	CST-45X ₁ -05X ₂	
	7 Wire	CST-45X ₁ -07X ₂	
	11 Wire	CST-45X ₁ -11X ₂	

Price term: EXW Shenzhen, validity: 3 months

X₁ stands for Trunking rail option: N/DC/E, X₂ stands for Color: WH/BK/SV, for details, please refer to order number list.
12832mm and 14248mm trunking rail only for full container load order

PERFEKTLIGHT

Luminaire



CTT: 3000K, 4000K, 5000K, 6000K

Lens: SP(Sharp-25°), NR(Narrow-60°), WD(Wide-90°), FF(Flat-140°)

DS(Double Asymmetric), RS/LS(Right/Left Asymmetric)

Power Factor: 0.95, CRI: >80Ra

Color Option: WH(White), BK(Black), SV(Silver)

Length	Power	Lumen	Code No.	VIP
570mm	16W	2400lm	CSL-0616-X ₁ X ₂ -05X ₃	
	26W	3900lm	CSL-0626-X ₁ X ₂ -05X ₃	
	32W	4800lm	CSL-0632-X ₁ X ₂ -05X ₃	
1416mm	40W	6000lm	CSL-1540-X ₁ X ₂ -05X ₃	
	65W	9750lm	CSL-1565-X ₁ X ₂ -05X ₃	
	80W	12000lm	CSL-1580-X ₁ X ₂ -05X ₃	
2832mm	65W	9750lm	CSL-3065-X ₁ X ₂ -05X ₃	
	80W	12000lm	CSL-3080-X ₁ X ₂ -05X ₃	
	120W	18000lm	CSL-3012-X ₁ X ₂ -05X ₃	
4248mm	96W	14400lm	CSL-4596-X ₁ X ₂ -05X ₃	
	120W	18000lm	CSL-4512-X ₁ X ₂ -05X ₃	

Price term: EXW Shenzhen, validity: 3 months

X₁ stands for CCT: 30/40/50/60, X₂ stands for beam angle: SP/NR/WD/FF, X₃ stands for Color: WH/BK/SV
There are 2 options for optic Lens & PC, Beam option for Lens: SP/NR/WD/FF, Beam option for PC: Clear/PCFF
12832mm and 14248mm luminaire only for full container load order

Function Module

Discription

Code No.

VIP

Dimming Driver



1-10V Dimming

CSX₁-X₂-10

DALI Dimming

CSX₁-X₂-DA

DALI PS

CSA-PS

Emergency Driver



with 6W output

CSD-E1

with 12W output

CSD-E2

Emergency Battery



1800mAh Battery

CSB1

3600mAh Battery

CSB2

Price Term: EXW Shenzhen, Validity: 3 months

X₁ stands for driver standard (American/European): 1/2, X₂ stands for Power Dimming and Emergency function demands (none/equipped with corresponding wires)

PERFEKTLIGHT

Function Module

Discription

Code No.

VIP

Sensor Module



570mm

10m detection

CSS-0610-X₁X₂-X₃

20m detection

CSS-0620-X₁X₂-X₃

1416mm


10m detection

CSS-1510-X₁X₂-X₃

20m detection

CSS-1520-X₁X₂-X₃

Track Rail Module



570mm

5 Wire

CST-06S-05X₂

7 Wire

CST-06S-07X₂

11 Wire

CST-06S-11X₂

1416mm

5 Wire

CST-15S-05X₂

7 Wire

CST-15S-07X₂

11 Wire

CST-15S-11X₂

Price Term: EXW Shenzhen, Validity: 3 months

X₁ stands for wire option: 05/07/11, X₂ stands for Color: WH/BL, X₃ stands for dimming option: DA/10
Sensor module options: Daylight / Microwave / Both

PERFEKTLIGHT

Accessory

Discription

Code No.

VIP

Feed In Box



5 Wire

CSN-B-05X₂

7 Wire

CSN-B-07X₂

11 Wire

CSN-B-11X₂

L Node Connector



5 Wire

CSN-LX₁-05X₂

7 Wire

CSN-LX₁-07X₂

11 Wire

CSN-LX₁-11X₂

T Node Connector



5 Wire

CSN-TX₁-05X₂

7 Wire

CSN-TX₁-07X₂

11 Wire

CSN-TX₁-11X₂

X Node Connector



5 Wire

CSN-XX₁-05X₂

7 Wire

CSN-XX₁-07X₂

11 Wire

CSN-XX₁-11X₂

* Mass Order Qty > 300pcs

Accessory

Discription

Code No.

VIP

Power Supply Module



570mm

CST-06PU-X₁X₂

1416mm

CST-15PU-X₁X₂

E27/E14 Light Module



570mm

CST-06E12-X₁X₂

1416mm

CST-15E12-X₁X₂

Blank Cover



PC - 570mm

CSA-BC-06X₂

CSA-BC-06SV

PC - 1416mm

CSA-BC-15X₂

CSA-BC-15SV

End Cap



with Coreshine LOGO
or Neutral

CSA-EC-X₂

Accessory

Discription

Code No.

VIP

Suspension Accessory



Cord-3m

CSA-CO-3000

Rod-1m

CSA-RO-1000

Chain-3m

CSA-CH-3000

Surface-Mounted Accessory



for surface mounting

CSA-SU

Mounting Clip



with hole of diameter
13.5mm

CSP-052807

Female Connector



5 Wire

CSA-FC-05

7 Wire

CSA-FC-07

Wire Connector



Single Wire Connector

CSA-SC

Accessory

Discription

Code No.

VIP

Feed In Connector



5 Wire

CSA-FN-05

7 Wire

CSA-FN-07

11 Wire

CSA-FN-11

Conduit Gland



M20*1.5mm, outlet 15.2mm

CSA-CG

Power Supply Cable



20A, 2.5mm²*3
L: 3000mm or customized

CSA-PL-3000

Cable Gland



M20*1.5mm, outlet 14.0mm

CSA-CC

Conduit



inner diameter 14.1mm
L: 2000mm or customized

CSA-CD-2000